

## PAINTCO MAGNA SPRAY PLASTER PUTTY 20000

### DESCRIPTION

- Paintco Magna Spray Plaster Putty is an exclusive, tenacious, high build and multifunctional coating. Noteworthy feature of this product is the incorporation of tough elastic and alkali resistant binder to withstand the vagaries of nature. These features enable the user to fill small dents and cracks and also to offer hard smooth surface of interior and exterior cement and plaster retaining simultaneously the breathing properties of emulsion paint system.

### PHYSICAL DATA

Pigments	:	Combination of lamellar as well as reinforcing extenders.
Appearance	:	Flat
Colour	:	Off White
No. of components	:	One
Specific Gravity	:	Approx. 1.70
Solids by volume	:	Approx. 53%
Drying time at 30°C	:	Dust dry : 30-45 mints Hard dry : 2 hours Recoat ability : 2 hours
Flash point	:	Nonflammable

### APPLICATION DATA

Application method	:	Pressure pot spraying (nozzle: approx. 0.6mm), trowelling and spatula application.
Type of thinner	:	Water
Percentage of thinner	:	5% max. by volume (depending on temperature, method of application and drying conditions)
Theor. coverage at 100 microns DFT:	:	3.1m <sup>2</sup> /kg

### Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

### REMARKS

- After priming the surface with Paintco Latex Primer Sealer 1201, sufficient number of coats of Paintco Magna Spray Plaster XL are to be applied to build up adequate film thickness.

### Note

APPLICATION OF EXCESSIVELY THICK COATS OF XL IS TO BE AVOIDED TO PREVENT CRACKING.