

## PAINTCO PENTO MASTIC SILK 13161

### DESCRIPTION

- Paintco Pento Mastic silk is an acrylic copolymer based product with outstanding washability , hiding power and color retention properties .It has good flow and gives a smooth durable silk finish.

### PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	silk finish
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.17
Solids by volume	:	Approx. 32 ± 2
Drying time at 30°C	:	Dust dry : approx. 30 minutes Hard dry : approx. 2 hours Next coat : after 2 hours
Flash point	:	Nonflammable.

### APPLICATION DATA

Application method	:	Airless spray , air spray , brush & roller
Air less spray data	:	Nozzle 0.015", pressure 150kg/cm2
Type of thinner	:	Water
Dry film thickness per coat	:	30 microns.
Theor. coverage at 30 microns DFT	:	10.66 m2 / litre

### SURFACE PREPARATION

- The surface of concrete, plasterwork and rendering shall be clean ,smooth dust and efforescent free prior to receiving any decorative treatment, for repair and maintenance remove damaged and loose paint by mechanical cleaning and dust off.

### REMARKS

- Paintco Pento Mastic silk paint is suitable for application on wood, hardboard, asbestos, cement, plaster, concrete, brickwork and precast gypsum.

### Priming Coats

- Apply Paintco Latex Primer Sealer 1201 followed by Paintco Magna Spray Plaster Putty 20000 for exterior use or either Stucco Putty 2241 or Wood And Wall Filler 2008 for interior use.
- Clean all tools with water.