

PAINTCO POLYURETHANE FILLER / 2 PACK 1951

DESCRIPTION

- Paintco Polyurethane filler/ 2 Pack is polyol / polyisocyanate combination based product with good filling and breathing properties. It has good sandability and it is nonlifting. It is specially recommended for steel and wood for exterior and interior.

PHYSICAL DATA

Pigments	:	Rutile titanium dioxide and functional extenders.
Appearance	:	Flat
Colour	:	Off white and grey
No. of components	:	Two
Mixing ratio by volume	:	Base : Hardener 4 : 1
Pot life after mixing at 30°C	:	Approx. 6 hours
Specific gravity	:	Approx. 1.56 (mixed.)
Solids by volume	:	Approx. 63% (mixed.)
Drying time at 30°C	:	Dust dry : approx 20minutes Dry for sanding : approx one hour Hard dry : approx. 6-8 hours
Flash point	:	26°C

APPLICATION DATA

Application method	:	Spatula or trowel
Type of Thinner	:	Thinner no. 322
Recommended DFT per coat	:	250 microns
Theor. coverage at 250 microns DFT:	:	2.52 m ² / litre

REMARKS

- Not to be applied below 5° c and or over relative humidity of above 80%.
- Do not use the mixed product after overnight storage.