

PAINTCO BITUMEN / COALTAR COMBINATION 6671

DESCRIPTION

- Paintco Bitumen / Coaltar Combination is a glossy bitumen paint with good water resistant properties, that can be applied in rather thick coats on interior and exterior concrete plaster and metal surfaces.

PHYSICAL DATA

Appearance	:	gloss
Colour	:	Black
No. of components	:	One
Specific gravity	:	Approx. 0.93
Solids by volume	:	Approx. 60%
Drying time at 30°C	:	Dust dry : approx.4hours Harddry : 24 hours

APPLICATION DATA

Application method	:	Airless spray , air spray and roller
Airless spray data	:	Nozzle 0.015, pressure 110-150 kg/cm ²
Type of Thinner	:	Thinner No. 211
Percentage of thinner	:	Airless spray : 5% max. by volume Air spray : 15% max. by volume Brush & roller : 10% max. by volume.
Recommended DFT	:	200 microns
Theor. coverage at 200 microns DFT:	:	3 m ² / litre

REMARKS

- Paintco Bitumen / Coaltar Combination can be airless spray at least in two coats , if applied by brush at least in three coats.
- Selection of application method and the percentage of thinner to be added depend on the dry film thickness described per coat.
- during application take normal precautions such as wearing safety gloves, face mask and eye shields. Application ventilation must be maintained with applying this product in confined spaces.