

## PAINTCO WOOD STAIN 77644

### DESCRIPTION

- Paintco Wood Stain is moisture regulating nonblistering and transparent material for the protection and decoration of wood. It is particularly developed for hot humid climate. It has fungicidal action on timber. Very suitable for application on woodwork for which a high quality standard is required.

### PHYSICAL DATA

Pigments	:	Light fast pigments and stearate
Appearance	:	Eggshell
Colours	:	Various colours as given on Paintco Wood Stain shade card
No. of components	:	One
Specific Gravity	:	Approx. 0.91
Solid by volume	:	Approx. 50%
Drying time at 30°C	:	Dust dry : approx. 2 hours Hard dry : approx. 10 hours Next coat : after 24 hours
Flash Point	:	39°C

### APPLICATION DATA

Application method	:	Air spray, brush and roller
Type of thinner	:	No. 211
Percentage of thinner	:	Air spray :5% max. by volume Brush and roller : 2%max.by volume
Dry film thickness per coat	:	30microns
Theor. coverage at 30microns DFT	:	16 m <sup>2</sup> /ltr

### REMARKS:

- Paintco Wood stain contains special fungicides and preservatives and so prior treatment of wood with wood preservative is not necessary. Application of Wood Sanding Sealer is to be avoided to ensure proper of Paintco Wood Stain to give desired effect. Paintco Wood Stain 77644 itself has sealing and sanding properties.