

PAINTCO ASEPTIC COATING 7245

DESCRIPTION

- Paintco Aseptic Coating is highly resistant to saponification and has excellent durability. After adequate drying, it provides a scuff proof washable surface with excellent semigloss appearance. It may also be used for areas where moisture condensation may occur. Suitable for plaster, drywalls and concrete. Presence of unique germicide makes it specially suitable for painting of hospitals and clinics.

PHYSICAL DATA

Pigments	:	Rutile Titanium dioxide and / or colour pigments and functional extenders.
Appearance	:	Semigloss
Colour	:	White
No. of components	:	One
Specific gravity	:	Approx. 1.20
Solids by volume	:	Approx. 34 %
Drying time at 30°C	:	Dust dry : approx. 30 minutes Hard dry : approx. 2 hours Recoatibility : after 2 hours
Flash point	:	Nonflammable

APPLICATION DATA

Application method	:	Airless spray, air spray, brush & roller
Type of Thinner	:	Water
Percentage of thinner	:	Airless spray : 5% max. by volume Air spray : 15% max. by volume Brush & roller : 10% max. by volume
Dry film thickness per coat	:	30 microns
Ther. Coverage at 30 microns DFT	:	11.3 m ² /ltr

Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

REMARKS

- Paintco Aseptic Coating when applied over properly primed surface will provide a smooth crater-free coating. Absence of voids or microholes prevents the growth of bacteria and maintains the surface clean and hygienic. The coating complies with current air pollution regulations and does not contain lead or hydrocarbon solvents.