

## PAINTCO ALKALI RESISTANT PRIMER (W.B) 1508

### DESCRIPTION

- Alkali resistant primer is a kind of emulsion paint with excellent alkali. resistance.
- As a primer suitable for use on interior and exterior substrates including masonry, concrete surfaces to seal the surface

### The features of this product

- Excellent alkali resistance
- Good adhesion
- Good water resistance
- Good fungus and bacteria resistance.
- Easy to apply and fast drying

### PHYSICAL DATA

Pigment	:	Alkali resistance pigment.
Appearance	:	matt
Colours	:	off White
Specific gravity	:	Approx. 1.25
Solids by volume	:	Approx. 45%
Drying time at 30° C	:	Dust dry : approx. 30 minutes Recoatibility : after 2 hours
Flash point	:	Nonflammable

### APPLICATION DATA

Application method	:	Air spray, brush and roller
Type of thinner	:	Water
Percentage of thinner	:	Air spray :10-15% max. by volume Brush & roller : 5% Max. by volume
Dry film thickness per coat	:	40 microns
Ther. coverage at 40 mic. DFT	:	11.25 m <sup>2</sup> / litre

### REMARKS

#### Surface Preparation

- The surface should be free from grit, dirt and grease. Fill hairline cracks and minor voids with Paintco Stucco Putty 2241. Or Paintco Magna Wall Filler 10000. (for interior surfaces) and Paintco Magna Spray Plaster Putty 20000. (for exterior surfaces). Sand with sand paper lightly and thereafter apply Paintco Alkali resistant primer thinned with water. for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

#### Subsequent coat

- Paintco Plastic Emulsion Interior 2579. (for interior) and Paintco Acrylic Exterior Emulsion 2622 (for exterior).
- Clean all tools with water immediately after use.
- The practical spreading rate may vary, depending on the porosity and roughness of the substrate.