

PAINTCO NC PUTTY 10602

DESCRIPTION:

- Paintco NC Putty is nitrocellulose based filler with excellent filling properties. Especially developed for interior and exterior use on wood and metal for correcting f surface defects and mechanically damaged areas. The minor cracks, voids and surface roughness can be corrected with high quality filling properties of ready mixed Paintco NC Putty. It is fast drying and has very good Sandability.

PHYSICAL DATA:

Pigments	:	Combination of selected fillers, titanium dioxide or red oxide
Appearance	:	Flat
Colour	:	Clear, off white, grey & red oxide
No. of components	:	One
Solids by volume	:	Approx. 42% (for colors) Approx. 25% (for clear)
Drying times at 30oC	:	Dust dry : approx. 10minutes Hard dry : approx. 2 hours Next coat : after 2 hours
Flash point	:	20°C

APPLICATION DATA:

Application method	:	Spatula or trowel
Dry film thickness	:	Depending upon surface
Theoretical coverage at 100 microns DFT	:	4.2 m2/liter. for colors. 2.5 m2/liter for clear

REMARKS:

- Paintco NC Putty is recommended on wood & metal surfaces. For interior & exterior use, spread Paintco NC Putty evenly using trowel or spatula to repair damaged surfaces.
- After completely drying, sand papering will result in uniform surface ready for priming.