

PAINTCO PLASTIC EMULSION INTERIOR 2579

DESCRIPTION

- Paintco Plastic Emulsion Interior is based on special copolymer intended for use in hot and humid areas. It is high quality material and produces a beautiful finish. Paintco Plastic Emulsion Interior is suitable for application on wood, hardboard, asbestos, cement, plaster, concrete, brickwood and precast gypsum. It has excellent hiding power and is available in full range of colours.

PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	matt
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.50
Solids by volume	:	Approx 43%
Drying time at 30°C	:	Dust dry : approx. 1 hour Hard dry : approx. 2 hours Recoatibility : after 2 hours
Flash point	:	Nonflammable.

APPLICATION DATA :

Application method	:	Airless spray , air spray , brush & roller
Airless spray nozzle	:	Nozzle 0.015, pressure 150kg/ cm ²
Type of thinner	:	Water
Percentage of thinner	:	Airless spray : 5% max. by volume Air spray : 15% max. by volume Brush & roller : 10% max. by volume.
Dry film thickness per coat	:	35 microns.
Theor. coverage at 35 microns DFT	:	12.28m ² / litre

Surface Preparation :

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

REMARKS :

Priming coats:

- On new surfaces apply Paintco Latex Primer sealer 1201 Followed by Paintco stucco putty 2241.
- clean all tools with water immediately after use.