

## PAINTCO WASHABLE EMULSION INTERIOR/EXTERIOR 2636

### DESCRIPTION

- Paintco Washable Emulsion interior/exterior is an acrylic copolymer based product which exhibits splendid performance in interior and exterior applications.
- Most prominent feature is the hydrophobic nature of its dry film which ensure excellent washability.
- Its high power, excellent flow and leveling, give gorgeous look to the wall and its resistance to saponification, presence of UV absorbing pigments and flexible polymer with fungicide on its backbone make the coating last for years in the most severe climatic conditions.

### PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	Matt
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.40
Solids by volume	:	Approx. 36 ± 2
Drying time at 30°C	:	Dust dry : approx. 30 minutes Hard dry : approx. 2 hours Recoatibility : after 2 hours
Flash point	:	Nonflammable.

### APPLICATION DATA

Application method	:	Airless spray , air spray , brush & roller
Air less spray data	:	Nozzle 0.015", pressure 150
Type of thinner	:	Water
Dry film thickness per coat	:	30 microns.
Theor. coverage at 30 microns DFT	:	12 m <sup>2</sup> / litre

### Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

### REMARKS

- Paintco Washable Emulsion Interior/Exterior paint is suitable for application on wood, hardboard, asbestos, cement, plaster, concrete, brickwork and precast gypsum.

### Priming Coats

- Apply Paintco Latex Primer Sealer 1201 followed by Paintco Magna Spray Plaster Putty 20000.
- Clean all tools with water.