

PAINTCO MAGIC TOUCH 12010

DESCRIPTION

- Paintco Magic Touch is a outstanding water borne decorative paint based on combination of special kind of acrylic emulsion and special effect pigment., which gives excellent appearance. It is specially designed for interior application.
- It has good washability , color stability, excellent metallic look and can be designed in to any kind depending upon choice.

Recommended Use :

- it can be used for interior design on concrete and cement surfaces prepared carefully over Paintco Magic Touch Base Coat or Paintco Roshan.

PHYSICAL DATA

Appearance	:	shine(metallic effect)
Colours	:	as per catalog
Specific gravity	:	Approx. 1.03
Solids by volume	:	Approx. 26%
Drying time at 30°C	:	Dust dry : approx. 15 minutes Full dry : approx. 24 hour
Water Resistant	:	Passes 7 days ASTM D 870
Chemical resistance	:	pass, household chemicals ASTM D-1308
Freeze Thaw Stability	:	pass 3 cycles, ASTM D-2243
Flash point	:	Nonflammable

APPLICATION DATA

Application method	:	roller special type scrapper
Type of thinner	:	Water
Percentage of thinner	:	not recommended
Dry film thickness per coat	:	40 microns.
Theor. Coverage at 40 microns DFT	:	6.5 m ² / litre

Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

Application Method

- Apply One Or two coat of Paintco Wood And Wall Filler.let it full dry. Apply one or two coat of Paintco Magic Touch Base Coat with same color as per catalog or one coat of Paintco Roshan and allow to dry. Apply one coat of Paintco Magic touch by roller to hide the surface . let it dry.for 5-6 hrs, .again apply second coat of Paintco Magic Touch by special recommended scrapper or trowel to make design and give it to final beautiful look.