

PAINTCO WOOD SANDING SEALER 440

DESCRIPTION

- Paintco Wood Sanding Sealer is modified alkyd based product having fungicidal properties. It fills pores of wood surface and facilitates sanding and suitable for sport and all purpose of wood floors .The sanded product is smooth, non porous and ready for subsequent painting

PHYSICAL DATA

| | | | |
|----------------------------------|---|-------------------------|------------|
| Pigment | : | Stearates | |
| Appearance | : | Hazy | |
| Viscosity @30°C | : | 7 ±1 Poise | |
| Specific Gravity | : | 0.81 ± 0.02 | |
| Finish | : | Matt | |
| Flash Point | : | 39°C | |
| Drying Time at 30°C | : | Dust Dry | : 3 hour |
| | | Hard Dry | : 24 hour |
| | | Dry for sanding | : 12 hours |
| Volume Solid % | : | Approx. 36 % | |
| Theor. Coverag at 30 microns DFT | : | 12 m ² /lit. | |

APPLICATION DATA

- Paintco Wood Sanding Sealer should be reduced to 20-25 sec. Consistency on ford cup B4 at 30°C before application by using thinner no 211. Recommended method of application is by air spray. Several coats of Paintco Wood sanding sealer are recommended to get smooth and non absorbent surface and thereby reducing the number of coats of clear varnish.

REMARKS

- Application of Paintco Wood Sanding Sealer is to be avoided if wood stain colour is required as Paintco Wood Stain 77644 itself gives same sealing properties