

PAINTCO EPOXY SEALER / 2 PACK 3993

DESCRIPTION

- Paintco Epoxy Sealer / 2 Pack is a two pack reactive product suitable for application on bare asbestos , cement , concrete and other similar materials. This sealer must be used to prevent the binder from being absorbed non-uniformly out of the subsequent coating by the substrate. (Absence of this sealer will lead to considerable absorption of binder of subsequent coats in the substrate resulting into inferior durability).

PHYSICAL DATA

Colour	:	Transparent Clear.
No. of components	:	Two
Mixing ratio by volume	:	Base : Hardener 4 : 1
Pot life after mixing at 25°C	:	Min. 8 hours.
Specific gravity	:	Approx. 0.97 (mixed.)
Solids by volume	:	Approx. 50% (mixed)
Drying time at 30°C	:	Dust dry : 3 hours maximum Next coat : after 16 hours but within 5 days.
Flash point	:	25°C

APPLICATION DATA

Application method	:	Airless spray , air spray , brush & roller
Airless spray data	:	Nozzle 0.015" , Pressure 140 kg / cm ²
Thinner	:	Thinner No. 477/1
Percentage of thinner	:	5% max. by volume.
Theor. coverage at 35 microns DFT	:	14.28 m ² / litre
		This product is not to be applied below 5°C

REMARKS

- Paintco Epoxy Sealer - 2Pack 3993 must be applied as a tie coat directly over the substrate to improve the adhesion and thereby durability of the paint system.
- Paintco Epoxy Sealer - 2Pack 3993 can be applied as glaze coat over Paintco Epoxy Matt or Semi gloss Coatings.