

## PAINTCO MAGANAMUR VINYL WALL COATING 1009

### DESCRIPTION

- Paintco Magnamur Vinyl Wall Coating is an air drying non saponifiable self priming wall paint based on special acrylic polymers , for interior and exterior use. It is intended for application on concrete, cement and asbestos elements as a superior coating.

### PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and / or colours
Colour	:	White and colours
Appearance	:	Flat
Specific Gravity	:	1.36 ±0.02
Volume Solid %	:	Approx. 47.5 %
Flash Point	:	26°C
Drying Time	:	Dust dry : Approx 2 hours Hard dry : Approx 6 hours Next coat : After 24
Flash point	:	26°C

### APPLICATION DATA

Application method	:	Airless spray, Spray, Brush and Roller
Airless spray data:	:	Airless spray, Nozzle 0.015" pressure 110- 140kg/cm <sup>2</sup>
Thinner	:	No 21
Percentage of thinner	:	Airless spray : 5%max. by vol. Air spray : 25 % max. by vol. Brush & Roller : 10%max. by vol.
Dry film thickness per coat	:	30 microns
Theoretical coverage at 30 Microns DFT	:	15.8 m <sup>2</sup> /liter

### REMARKS

- Paintco Magnamur Vinyl Wall Coating has excellent water and chemical resistance. It is an ideal coating for kitchen and bathroom. May be applied over exterior concrete or plaster as a finish coat. The first coat (primer) should be 30% diluted with thinner No.21, so that penetration into the surface occurs. For subsequent coats only 10% reduction with thinner No.21.
- Paintco Magnamur Vinyl Wall Coating is resistant to water vapour and smokes. This paint has good antibacterial and fungicidal properties