

**DESCRIPTION :**

Paintco AFNOOR is a prestigious and attractive decorative finish for interior design. featuring an extraordinary brilliance derived from glowing and precious crystals; with some other pigments that give an elegant, charming and diamond effect

It is waterborne product exhibiting good washability and color stability

**PHYSICAL DATA :-**

Appearance	:	glowing diamond effect
colors	:	as per catalog
Specific gravity	:	Approx. 1.35
Solids by volume	:	Approx. 48 %
Drying times at 30oC	:	Dust dry : approx. 30 minutes Full dry : approx. 24 hour
Water Resistant	:	Passes 7 days ASTM D 870
Flash point	:	Nonflammable

**APPLICATION DATA :**

Application method	:	special trowel
Type of thinner	:	Water
Percentage of thinner	:	not recommended
Dry film thickness per coat	:	125 microns.
Theor. Coverage at 250 microns DFT :	:	1.90 m <sup>2</sup> / liter

**Surface Preparation:**

All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence. For repair and maintenance, remove damaged and loose particles mechanically and dust it off.

**Application Method :**

1. prepare the surface properly and apply one coat of paintco latex primer sealer 1201 or paintco alkali resistant primer 1202
2. apply one or two coats of paintco stucco putty 2241 or paintco wood and wall putty 2008
3. apply one coat of AFNOOR primer
4. apply two coats of paintco AFNOOR by using special recommended trowel and give enough time for each coat to dry completely.
5. Shadows and special effects can be generated by passing the trowel on the final coat while it is wet

The above information is based on our practical experience, given in good faith. It does not constitute a guarantee for individual application because the application and handling in each case lie control. We can not accept responsibility or liability for any damage also connection with the use of the product relative to coverage performance or injury.