

PAINTCO STRUCTURE SPRAY PLASTER 1-2 MM 11003

DESCRIPTION

- Paintco Structure Spray Plaster 1-2 MM is a coating designed for giving grandeur to individual's household property and is suitable for exterior concrete and plaster surface. It is an air drying coating devoid of lime and cement.
- A commendable feature of this product is that it gives high film thickness per coat without any cracking problem under severe climate conditions. Longevity of this coating coupled with labour saving application are the outcome of effective combination of its constituents.

PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	Flat, medium coarse texture finish
Colours	:	White and colours
Specific gravity	:	Approx. 1.75
Solids by volume	:	Approx. 65%
Drying time at 30°C	:	Dust dry : approx. 4 hours Hard dry : approx. 24 hours Next coat : after 12 hours
Flash point	:	Nonflammable.

APPLICATION DATA

Application method	:	Air spray & airless spray.
Type of thinner	:	Water
Percentage of thinner	:	5% max. by volume
Coverage	:	1.3 - 1.8 Kg / M ² (depending on the surface condition and desired structure).

REMARKS

- Paintco Structure Spray Plaster 1-2 MM provides an ideal decorative finish to precast concrete areas. It is suitable for application on gypsum board and plaster. Especially developed for humid climate areas, providing long life without maintenance. For better coverage apply one coat of Paintco Latex Undercoat 1222 in place of Paintco Latex Primer Sealer 1201. Application details regarding airless spraying are available upon request.

NOTE

- A coat of Paintco Aliphatic PU Enamel / 2 Pack 6650 is Recommended. This will also help to minimize dust collection and to give excellent color retention property to the coating under exterior / interior exposure.