TECHNICAL DATA



PAINTCO PROFILETEX 11014

DESCRIPTION

• Paintco PROFILE TEX Finish is a novelty coating designed for giving grandeur to the building and is suitable for exterior concrete and plaster surface. It is an air drying coating devoid of lime and cement.

 A commendable feature of this product is that it gives novel outlook to the surface, along with long term protection.

PHYSICAL DATA

Pigment : Rutile Titanium Dioxide and or/

Colour pigment and functional extenders.

Appearance : Flat

Colour : Off White and colours Specific gravity : Approx. 1.75-1.80

Solids by volume : Approx. 70%

Drying times at 30°C : Dust dry : approx. 1 hour : Hard dry : approx. 24hours

Flash point : Nonflammable.

APPLICATION DATA:

Application method : Application with special applicator.

Type of Thinner : Sweet Water
Percentage of thinner : 5% max. by volume
Theor. coverage @ 3mm DFT : 0.34 square meter/Kg.

Surface Preparation

 All surfaces must be thoroughly prepared and clean and should be free from alkali and efforescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

REMARKS

- Paintco Profiltex Finish provides an ideal decorative finish to precast concrete areas. It is suitable for application on gypsum board and plaster.
- Paintco latex primer sealer 1201 or alkali resistant primer 1507 are recommended as a primer coat.