

PAINTCO UNDERCOAT ENAMEL 1225

DESCRIPTION

- Paintco Undercoat enamel is based on special modified alkyd resins which make it suitable for interior and exterior use. It is suitable for use as an intermediate coat over primed metal, sealed wood and primed concrete prior to top coating. Under coat Enamel gives excellent covering capacity, hiding power and adhesion. It is available in a wide range of colours.

PHYSICAL DATA

Pigment	:	Titanium Dioxide or Color Pigments
Appearance	:	Flat
Colours	:	White, full range available
No, Of Components	:	One
Specific Gravity	:	Approximately 1.40
Solid By Volume	:	Approximately 52 %
Drying time at 30 Degrees	:	Dust Dry : Approximately 60 Hard Dry : Approx 10 hours
Recoatibility	:	Overnight
Flash Point	:	39Degree C

APPLICATION DATA

Application Method	:	Air spray, Brush or Roller
Type of Thinner	:	Thinner No. 211
Percentage of Thinner	:	Air Spray :10%Max by Volume Brush & Roller :5% Max by Volume
Dry Film thickness	:	Approximately 30 Microns per coat
Theo. Coverage@ 30 microns DFT.	:	Approximately 17 square meters per Lit

REMARKS

- Paintco Undercoat Enamel 1225 makes the ideal combination with the following products:
- Paintco High Gloss Enamel 1226 Or
- Paintco Satin Finish 1129 Or
- Paintco Flat Alkyd 1544
- CLEAN TOOLS WITH THINNER NO.211