

## PAINTCO SATIN/EGG SHELL FINISH 1129

### DESCRIPTION

- Paintco Satin Finish is a lustrous coating which eliminates eye-straining glitter of glossy coatings as well as dull matt appearance of flat finishes.
- Secondary flow characteristic of polymer present in this product promotes flow and leveling to ensure opacity smooth surface and also sag free appearance.
- Stain resistance and sheen are optimized and combined with durability under interior and exterior conditions when applied over suitably primed cement, plaster, wood and steel.

### PHYSICAL DATA

Pigment	:	Titanium dioxide and /or colour pigments and functional extenders
Appearance	:	Semi gloss/Eggshell
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.25
Solids by volume	:	Approx. 47%
Drying time at 30°C	:	Dust dry : approx. 2 hours Hard dry : approx. 10 hours Recoatibility : overnight
Flash point	:	39°C.

### APPLICATION DATA

Application method	:	Air spray, airless spray , brush and roller
Airless spray data	:	Nozzle 0.013, pressure 150kg /cm <sup>2</sup>
Type of thinner	:	Thinner No. 211
Percentage of thinner	:	Airless spray : 3% max. by volume Air spray : 15 % max. by volume Brush & roller : 5% Max. by volume
Dry film thickness per coat	:	30 microns
Ther. coverage at 30 mic. DFT	:	15.6 m <sup>2</sup> / litre

### Priming coats

- For cement and plaster surfaces : Paintco Latex Primer Sealer 1201.
- For ferrous metal : Metal Primer 3010
- For nonferrous metal a suitable Metal Primer after pretreatment with Etch Primer / 2pack 3255
- For wood surfaces : Paintco Wood & Wall Primer 1333
- Clean tools with thinner No. 211.
- Airless spray information is for guidance only and subject to adjustment.