

PAINTCO STUCCO PUTTY 2241

DESCRIPTION

- Paintco Stucco Putty is a plastic Putty with good filling properties. It is suitable for interior use on cement and concrete structures for rectifying surface defects and for repairing mechanically damaged areas. The minor cracks, voids and surface roughness can be eliminated with high quality filling properties of ready mixed Paintco Stucco Putty.

PHYSICAL DATA

Pigment	:	Combination of selected fillers
Appearance	:	Flat
Colours	:	Off White
No. of components	:	One
Specific gravity	:	Approx. 1.73
Solids by volume	:	Approx. 54%
Drying time at 30°C	:	Dust dry : approx. 30 minutes (depending on WFT) Hard dry : approx. 2 hours (depending on WFT) Next coat : after 2 hours
Flash point	:	Nonflammable.

APPLICATION DATA

Application method	:	Spatula or trowel
Type of thinner	:	Water
Percentage of thinner	:	Depending on kind of use and temperature
Dry film thickness per coat	:	100 microns per coat (max. 500 microns)
Ther. coverage	:	3.2 m ² /kg at 100 microns DFT

REMARKS

- Paintco Stucco Putty is used on walls and ceilings for interior plastering and repair of damaged surfaces. Ideal for areas of high moisture content, kitchens and bathrooms. Use spatula or trowel to spread Stucco Putty evenly. The slow drying nature of Stucco Putty allows several over coatings before hard setting. When hard dry, sand with sand paper lightly until uniformly rough.
- Apply Paintco Latex Primer Sealer 1201 over paintco stucco putty followed by at least 2 coats of Paintco Plastic Emulsion Interior or Paintco Enamel Gloss, Semi gloss or flat.
- In addition to its normal use on cement and concrete it is specially suitable for interior use on precast concrete structures.