

## MARBLE FINISH 2244

### DESCRIPTION

- Marble putty is a novelty finish designed for giving intricate patterns with its natural beauty and attractive colours. It creates different and unique effect on any surface like, cement, concrete, blocks, plastered walls, wooden pattern, pipes or plaster faced pillars etc. It is an air-drying coating.
- A commendable feature of this product is that it gives marble effect to the surface, along with long-term protection.

### PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and/ or colour pigments and functional extenders
Appearance	:	Glossy
Colours	:	White and colours
Solids by volume	:	54%
Drying time at 30°C	:	Dust dry : App.30 min. Hard dry : App.4 Hours
Flash point	:	Non- flammable

### APPLICATION DATA

Application Method	:	Stainless Steel Trowel or Spatula
Type of Thinner	:	Water

### APPLICATION METHOD:-

- Surface on which marble finish is applied has to be sound, clean dry and completely free from dust, dirt, oil and contaminants .
- Apply a coat of Paintco latex primer sealer or Paintco wall primer.
- Apply one coat of Paintco stucco putty to fill the imperfections and obtain an smooth surface.
- Apply two coats of Paintco interior emulsion or Paintco washable emulsion with roller.
- Apply marble putty on to small area using spatula, then apply the same Across the entire surfaces using a scraper and Let it dry
- Repeat the same process of application two times to obtain a very smooth marble like finish.
- can create different patterns by controlling the direction of scraper such as wavy lines. Cross lines or diagonal patterns. When dry sand the surface with 1000 abrasive papers.
- Finally create the marble effect by polishing with the steel trowel.

### Note

- polishing will bring out the glossy and dark/light effects by increasing the polishing.

### Remarks :

- Paintco Marble Putty creates the marble effect by polishing with the spatula. Ensure that all areas are polished smoothly.