TECHNICAL DATA



PAINTCO ACRYLIC EMULSION NON DRIP 7243

DESCRIPTION

Paintco Acrylic Emulsion Non Drip is based on special acrylic copolymer and flow modifiers. It has
Excellent colour retention and gloss retention which give always a new look to the painted surface after
slight mopping with wet cloth. It is ideally suitable for interior and exterior uses. Flow and leveling are
phenomenally good. This product give the non-drips properties.

PHYSICAL DATA

Pigments : Rutile Titanium dioxide and /or colour pigments

Appearance : Gloss, S/gloss
Colour : White and colours

Number of components : One

Specific gravity : Approx. 1.15 Solids by volume : Approx. 31%

Drying time at 30°C : Dust dry : approx. 30 minutes

Hard dry : approx. 4 hours Next coat : After 4 hours

Flash point : Nonflammable

APPLICATION DATA

Application method : brush & Roller
Type of thinner : Water
Percentage of thinner : 5% if required
Dry film thickness per coat : 40microns

Theor. coverage at 40 microns DFT: approx.7.75m² /litres

Surface Preparation

 All surfaces must be thoroughly prepared and clean and should be free from alkali and efforescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

Remarks

- Apply Paintco Latex Primer Sealer 1201 or Paintco Alkali Resistant Primer 1507 followed by Paintco wall filler 10000 for interior or Paintco Magna Plaster Putty 20000 for exterior.
- · Paintco Acrylic Emulsion Non-Drip is extraordinary good for stain and burnish resistance.