TECHNICAL DATA

Paintco Since 1975 Lealtill History

PAINTCO SAKHER 1511

DESCRIPTION

Paintco SAKHER is water borne texture finish based on pure acrylic and U.V resistant natural color aggregates, giving archetype beauty to the exterior walls.

A commendable feature of this product is, excellent durability, resists alkali, atmospheric pollutants and harsh climatic condition of Middle East.. it is APEO, formaldehyde and ammonia free. Longevity of this coating enhanced by over coating of Paintco Acrylic Matt Clear.

PHYSICAL DATA :-

Pigment: natural color aggregates and functional extenders

Appearance: multicolor texture Specific gravity: Approx. 1.60 ± 0.03

Solids by volume: Approx.60 %

Drying times at 30oC : Dust dry: approx. 1 hour

full dry: approx. 24hours

Flash point: Nonflammable.

Water resistance: passes 7 days (ASTM D870)
Color retention: excellent (no color change)

Weather resistance: passes (ASTM G-53)

APPLICATION DATA:

Application method: hopper gun and smooth plastic roller

Type of Thinner: Sweet Water Nozzle size: 2.5-3.0 mm Air pressure: 70-90 psi

Percentage of thinner: depending on the weather condition and application condition

Theor. coverage: 0.25- 0.30 square meter/ Kg.

(depending on surface condition and thickness of the coat)

SURFACE PREPARATION:

New surface must be cured at least 28 days prior to application . All surfaces must be thoroughly prepared ,clean and should be free of alkali and efforescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off. Recommend to be used over Paintco latex primer sealer.

PAINTING SYSTEM:

Paint should be stirred properly before use. Apply one coat of paintco latex primer sealer and leave it for full dry. Apply paintco sakher with hopper gun in proper and even thickness.

Press with smooth plastic roller, when the product is dry to touch. Then let it fully dry.

Apply one coat of Paintco Acrylic Clear matt after hard dry.

REMARKS:

Paintco Sakher is Ideal for exterior application. It is also suitable for application over primed concrete, cement and brick surface.

The above information is based on our practical experience, given in good faith. It does not constitute a guarantee for individual application because the application and handling in each case lie control. We cannot accept responsibility or liability for any damage also connection with the use of the product relative to coverage performance or injury.