

PAINTCO FLAT ALKYD PAINT 1544

DESCRIPTION

- Paintco Flat alkyd Paint is high quality paint providing a complete flat finish which is suitable for interior and exterior decorative coatings for cement and plaster surfaces. It is also suitable for Metal and Wood pretreated which suitable Primer and Under coat Enamel. Controlled thixotropic nature of binder facilities ease of application, freedom from sagging, flow and leveling of film. This product also gives tough, durable, washable and burnish resistant film. It complies with SASO's Standard for Enamel Paints.

PHYSICAL DATA

Pigment	:	Titanium dioxide and /or colour pigments and functional extenders
Appearance	:	Flat
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.36
Solids by volume	:	Approx. 49%
Drying time at 30°C	:	Dust dry : approx. 1 hour Hard dry : approx. 10 hours Next coat : overnight
Flash point	:	39°C.

APPLICATION DATA

Application method	:	Air spray, airless spray , brush and roller
Airless spray data	:	Nozzle 0.013, pressure 150kg /cm ²
Type of thinner	:	Thinner No. 211
Percentage of thinner	:	Airless spray : 3% max. by volume Air spray : 10% max. by volume Brush & roller : 5% Max. by volume
Dry film thickness per coat	:	30 microns
Ther. Coverage at 30 mic. DFT	:	16.3 m ² /litre

Priming coats

- For cement and plaster surfaces: Paintco Latex Primer Sealer 1201.
- For ferrous metal: Paintco Metal Primer 3010.
- For nonferrous metal a suitable Metal Primer after pretreatment with Paintco Etch Primer/2pack 3255.
- For wood surfaces: Paintco Wood & Wall Primer 1333.
- Clean tools with thinner No. 211.
- Airless spray information is for guidance only and subject to adjustment.