

PAINTCO ULTRA PRIMER / 2 K 28526

DESCRIPTION

- Paintco Ultra Primer 2 K is a premium fast drying , high build primer surface especially formulated for use with Ultra H.S/2K top coats in automotive refinish. Main feature of this products is easily sanding and excellent adhesion to properly prepared surfaces and minimum settling of the thinned primer in the spray pot overnight.

PHYSICAL DATA

Pigments	:	Rutile titanium dioxide and /or color pigments and functional extenders.
Appearance	:	matt
Colour	:	white & grey
No. of components	:	Two
Mixing ratio by volume	:	Base : Hardener 3 : 1
Pot life after mixing at 30°C	:	6 hours
Specific gravity	:	Approx. 1.3 (mixed.)
Solids by volume	:	Approx. 43% (mixed.)
Drying times at 30°C	:	surface dry : 30 min Dry to sand approx 60mts depending on film build and ambient conditions
Flash point	:	21°C

APPLICATION DATA

Application method	:	Airless spray or air spray
Type of Thinner	:	Ultra Thinner 326
Percentage of thinner	:	Airless spray : 3-5% max. by volume Air spray : 25 % max. by volume
Application Viscosity	:	17-20 sec
Recommended DFT per coat	:	40 microns
Theor. coverage at 40 microns DFT	:	Approx. 10.75 m ² / litre

REMARKS

- Not to be applied below 5oC and /or above relative humidity of 80%