

PAINTCO WOOD AND WALL PRIMER 1333

DESCRIPTION

- Paintco Wood and Wall Primer is a modified alkyd based primer for wood, cement plaster, concrete and gypsum board surfaces. It has excellent covering capacity, hiding power and adhesion. Ideally suitable for exterior and interior use. It has very good sealing and priming properties and sandable when hard dry.

PHYSICAL DATA

Pigments	:	Rutile titanium dioxide and fillers
Appearance	:	Flat
Colour	:	White
No of components	:	One
Specific gravity	:	Approx. 1.40
Solids by volume	:	Approx. 52.5%
Drying time at 30°C	:	Dust dry : approx. 2 hours Hard dry : approx. 8 hours Next coat : overnight
Flash point	:	39°C.

APPLICATION DATA

Application method	:	Airless spray, air spray, brush and roller
Airless spray data	:	Nozzle size 0.015, pressure 150 kg/cm ²
Type of thinner	:	Thinner no. 221
Percentage of thinner	:	Airless spray : nil Airspray : 10% max. by volume Brush and roller : 5% max. by volume
Recommended Dry Film Thickness	:	40 Microns
Theor. Coverage @40 mic. thickness:	:	13.12 square meter/ lit..

Surface preparation:

- Clean wood surface after sanding down. Clean all plaster and block walls. For absorbent substrates one coat of Paintco Wood and Wall Primer 1333 20% thinned with thinner no. 221 should be applied.

Subsequent coats:

- Two coats of Paintco Enamel Paint (gloss, semigloss and flat) or Paintco Emulsion Paint (interior or exterior) Clean all tools with thinner no.221. Not to be applied over fresh cementitious surface with high alkalinity.