

PAINTCO SPATTERCOAT TEXTURE FINISH 11005

DESCRIPTION

- Paintco Spattercoat Texture Finish is an acrylic copolymer based sprayable, air and aggregate free texture paint. It is suitable for application on concrete or plastered surfaces. Excellent smooth texture such as “Orange Peel” effect may be achieved by adjustment of consistency of the coating using water and by regulating the air pressure of the spray equipment.

PHYSICAL DATE

Pigments	:	Rutile titanium dioxide and functional extenders
Appearance	:	Flat
Colours	:	Off White
No. of components	:	One
Specific gravity	:	approx. 1.50
Solids by volume	:	approx. 55%
Drying time at 30° C	:	Dust dry : approx. 1 hour Hard dry : approx. 24hours Next coat : after 12 hours
Flash point	:	Nonflammable

APPLICATION DATA

Application method	:	Hopper gun
Type of thinner	:	Water
Percentage of thinner	:	5 %max. by volume(if required)
Spray Data	:	Hopper Gun Nozzle Size :5-7 mm Air Pressure : 4-6 bar
Theor. Coverage	:	1 - 1.2 m ² /kg (depending on surface condition)

Special pressed pattern can be achieved by using plastic roller before the sprayed coating dries completely)

REMARKS

- The surface must be thoroughly cured, clean and dry before application of Paintco Spattercoat Texture Finish. To achieve overall uniform finish, it is recommended that the surface should be primed with Paintco Latex Primer Sealer 1201, Paintco Latex Undercoat 1222 or Paintco Alkali Resistant Primer 1507.
- During spray application, reduce air pressure and adjust consistency of the to obtain satisfactory spatter pattern. Hold the gun near the surface and coat evenly with circular movement of hand.

Subsequent coats

- Water based emulsion paints of solvent based finishes such as conventional Paintco Gloss Enamel. For excellent color retention Paintco Aliphatic P.U. Enamel / 2pack 6650 should be applied as a top coat.
- The surface must be sound, clean and free from all contaminants.
- Clean all tools with water.