

**PAINTCO REMAL 12044**

**DESCRIPTION :**

Paintco Remal is a outstanding water borne decorative paint based on combination of special kinds of acrylic binder and special type of effect pigment to create a desert effect on walls providing dignified beauty

It has good washability , color stability, excellent metallic effect resemblance.

**Recommended Use :** it is specially designed for interior application as a finish coat over Remal Primer on concrete , gypsum & cement surfaces. It is suitable for interior walls of hotels , showroom galleries, offices, palaces etc.

**PHYSICAL DATA :-**

Appearance	:	metallic effect colors
colors	:	as per catalog
Specific gravity	:	Approx. 1.00
Solids by volume	:	Approx. 35 %
Drying times at 30°C	:	Dust dry : approx. 15 minutes Full dry : approx. 4 hour Hard dry : 24 hours
Water Resistant	:	Passes 7 days ASTM D 870
Flash point	:	Nonflammable
Shelf life (in sealed container)	:	12 months in a dry and well ventilated place

**APPLICATION DATA :**

Application method	:	special brush
Cleaning tools	:	fresh Water
Percentage of thinner	:	not recommended
Theoretical Coverage	:	4-5 m <sup>2</sup> / litre

**SURFACE PREPARATION:**

New surface must be cured at least 28 days prior to application . All surfaces must be thoroughly prepared ,clean and should be free of alkali and efflorescence,  
for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

**APPLICATION METHOD**

1. prepare the surface properly and apply one coat of paintco latex primer sealer 1201 or paintco alkali resistant primer 1202
2. apply two coats of paintco stucco putty 2241 or paintco wood and wall putty 2008
3. apply two coat of Paintco Remal Primer of the same color of Remal top coat by using fine roller or spray gun to get a smooth surface without roller marks.
4. apply one coats of Paintco Remal obliquely in up down movement by using special recommended brush .

The above information is based on our practical experience, given in good faith. It does not constitute a guarantee for individual application because the application and handling in each case lie control. We can not accept responsibility or liability for any damage also connection with the use of the product relative to coverage performance or injury.