

PAINTCO ACRYLIC EMULSION INTERIOR/EXTERIOR 2635

DESCRIPTION

- Paintco Acrylic Emulsion Exterior exhibits outstanding weather resistance , excellent hiding power and flexibility properties making it suitable for exterior and interior use. It is also highly resistant to saponification which makes it suitable for comparatively new plaster. After adequate drying , it provides a scuff proof washable surface. It is specially suitable for interior areas where moisture condensation may occur, also it is recommended for application on wood, hardboard, asbestos , cement , plaster , concrete , brickwork and precast gypsum.

PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	Flat
Colours	:	White and colours
Specific gravity	:	Approx. 1.46
Solids by volume	:	Approx. 36%
Drying time at 30°C	:	Dust dry : approx. 15 minutes Hard dry : approx. 1 hour Recoatibility : after 2 hours
Flash point	:	Nonflammable.

APPLICATION DATA

Application method	:	Airless spray , air spray , brush & roller
Type of thinner	:	Water
Percentage of thinner	:	Airless spray : 3% max. by volume Air spray : 10% max. by volume Brush & roller : 5% max. by volume.
Dry film thickness per coat	:	30 microns.
Theor. coverage at 30 microns DFT	:	12 m ² / litre

Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

Priming Coats:

- Apply Paintco Latex Primer Sealer 1201 followed by Paintco Wall Filler 10000 (for interior) and Paintco Magna Spray Plaster Putty 20000 (for Exterior)
- Clean all tools with water.