

PAINTCO NC PRIMER 10519

DESCRIPTION

- Paintco NC Primer is a rapid drying sprayable suitable for wood and metal. The resultant finish is sandable, hard and durable. It withstands handling in works within a short period after application. It must be over coated with suitable finish coating after sanding.

PHYSICAL DATA

Pigments	:	Rutile titanium dioxide and /or color
pigments	:	Functional extenders.
Appearance	:	Matt
Colour	:	White & Grey and red oxide
Specific gravity	:	Approx. 1.30
Solids by volume	:	Approx. 34%
Drying times at 30oC	:	Dust dry : 10-15minutes
	:	Hard dry : 60minutes
Thinner	:	Lacquer thinner
Theoretical coverage at 30Microns DFT	:	11.3 m ² /litre
Flash point	:	20°C

APPLICATION DATA

- Paintco NC Primer may be reduced with Paintco Lacquer Thinner to about 20 sec. on Ford Cup B4 / 30oC and apply by air assisted conventional spray machine. Dry film thickness of minimum 30 microns would be adequate.

REMARKS:

- We recommend that the surface should be thoroughly cleaned before application of Paintco NC Primer.
- For nonferrous metals, one coat of Paintco Etch Primer /2pack P-3255 is essential before application of Paintco NC Primer.
- The product is flammable and proper care should be taken during storage and use.
- Before applying Paintco NC Primer, trowel application of Paintco NC Putty is desirable to remove any imperfections on the surface.