

## PAINTCO TEXTURE GLOSS 11006

### Description

- Paintco Texture Gloss is a water coating based on highly flexible acrylic copolymer. The product is formulated to provide protective and decorative structure on plastered and precast concrete walls. It does not contain sand or quartz and the structure achieved is smooth. It is ideally suitable for interior and exterior uses. After drying the coating is scuffproof and washable. The gloss retention is also excellent and the smooth surface remains free from accumulated dust and dirt.

### PHYSICAL DATE

Pigments	:	Rutile titanium dioxide or colour pigment
Appearance	:	Texture smooth finish
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	1.12
Solids by volume	:	38%
Drying time at 30°C	:	Dust dry : 1 hour Hard dry : 4hours
Flash point	:	Nonflammable

### APPLICATION DATA

Application method	:	Sponge roller
Type of thinner	:	Water
Percentage of thinner	:	5%max. by volume
Recommended DFT	:	100 microns (average)
Rate of coverage at 100micronsDFT	:	3.8m <sup>2</sup> /ltr

### REMARKS

- The surface to be painted must be sound, clean and free from all contaminants. Ideally the should be sealed with Paintco Latex Primer Sealer 1201. Apply Paintco Texture Gloss with sponge roller directly from cans without thinning. However, to facilitate application small quantity of water not more than 5% by volume should be added. Use of other type of rollers can distinctly provide different structure.
- Immediately after drying, the surface may appear slightly tacky which does not persist after a day. However, the surface remains permanently flexible, supple and soft touch.