

## PAINTCO PENTO MASTIC GOLD 2640

### DESCRIPTION

- Paintco Pento Mastic Gold is an special pure acrylic based product which exhibits splendid performance in interior applications.
- Most prominent feature is the hydrophobic nature of its dry film which ensure excellent flow properties , leveling and washability.
- Its high power, excellent flow and leveling, give gorgeous look to the wall and it is resisting to saponification. Pentomastic gold also offers resistance against bacterial and fungal growth on interior walls and is approved by IMSL lab (U.K) Industrial microbiological service ltd .

### PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	Eggshell
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.30
Solids by volume	:	Approx. 38 ± 2
Drying times at 30oC	:	Dust dry : approx. 30 minutes Hard dry : approx. 2 hours Next coat : after 2 hours
Flash point	:	Nonflammable.

### APPLICATION DATA

Application method	:	Airless spray , air spray , brush & roller
Air less spray data	:	Nozzle 0.015, pressure 150kg/cm <sup>2</sup>
Type of thinner	:	Water
Dry film thickness per coat	:	40 microns.
Theor. coverage at 40 microns DFT	:	9.5m <sup>2</sup> / litre

### SURFACE PREPARATION

- The surface of concrete, plasterwork and rendering shall be clean ,smooth dust and efforescent free prior to receiving any decorative treatment, for repair and maintenance remove damaged and loose paint by mechanical cleaning and dust off.

### REMARKS

- Paintco Pento Mastic Gold paint is suitable for application on wood, hardboard, asbestos, cement, plaster, concrete, brickwork and precast gypsum.

### Priming Coats

- Apply Paintco Latex Primer Sealer 1201 followed by Paintco Magna Spray Plaster Putty 20000.
- Clean all tools with water.