

PAINTCO ACRYLIC EMULSION EXTERIOR 2622

DESCRIPTION

- Paintco Acrylic Emulsion Exterior exhibits outstanding weather resistance , excellent hiding power and flexibility properties making it suitable for exterior use. It is also highly resistant to sponification which makes it suitable for comparatively new plaster. After adequate drying , it provides a scuff proof washable surface. It complies with SASO's Standard for Emulsion Paints.

Recommended Use

- Acrylic Emulsion Exterior is suitable for interior areas where moisture condensation may occur and recommended for application on wood, hardboard , asbestos , cement , plaster , concrete , brickwork and precast gypsum.

PHYSICAL DATA

Pigment	:	Rutile titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	Semi Flat
Colours	:	White and colours
Specific gravity	:	Approx. 1.48
Solids by volume	:	Approx. 36%
Drying time at 30° C	:	Dust dry : approx. 15 minutes Hard dry : approx. 1 hour Recoatibility : after 2 hours
Flash point	:	Nonflammable

APPLICATION DATA

Application method	:	Airless spray , air spray , brush & roller
Type of thinner	:	Water
Percentage of thinner	:	Airless spray : 5% max. by volume Air spray : 10% max. by volume Brush & roller : 5% max. by volume.

Dry film thickness per coat	:	30 microns.
Theor. coverage at 30 microns DFT	:	12 m ² / litre

Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

REMARKS :

- Recommended to be used over Paintco Latex Primer Sealer 1201 or Paintco Latex Undercoat 1222 followed by Paintco Magna Spray Plaster Putty 20000.
- clean all tools with water immediately after use.