

PAINTCO WOOD AND WALL PUTTY 2008

DESCRIPTION

- Paintco wood and wall putty is a quality plastic putty having excellent filling and levelling properties. It is ready to use paste for smoothing the internal and external concrete surfaces. and has easy workability. It is suitable for interior/exterior use on wood, cement and concrete structures for repairing mechanically damaged areas and for rectifying surface defects such as cracks, blowholes and surface roughness.

PHYSICAL DATA

Pigment	:	Combination of selected fillers
Colors	:	Creamy Off White
Consistency	:	Thick Paste
No. of components	:	One
Specific gravity	:	Approx. 1.72-1.77
Solids Content	:	Approx. 70-73%
Drying time at 30°C	:	Dust dry : approx. 30mts Hard dry : approx. 2 hours

Note :

Drying time depending upon the condition of surface.

Flash point	:	Nonflammable.
-------------	---	---------------

APPLICATION DATA

Application method	:	Spatula or trowel
Type of thinner	:	Water(If required)
Percentage of thinner	:	Depending on kind of use and temperature
Dry film thickness per coat	:	100 microns per coat
Theoretical coverage	:	3.0 --3.2 m ² /kg at 100 microns DFT

REMARKS

- Paintco wood and wall putty is used on wood, walls and ceilings for plastering and repair of damaged surfaces. Ideal for areas of high moisture content, kitchens and bathrooms. Use spatula or trowel to spread the putty evenly. When hard dry, sand with suitable sand paper lightly to get smooth finish.
- In addition to its normal use on wood, cement and concrete. It is specially suitable for interior/exterior use on pre casted concrete structures.