

## PAINTCO MISHNU 12035

### DESCRIPTION :

Paintco Mishnu is a outstanding water borne decorative paint based on combination of special kinds of acrylic binder and special quality aggregates , which creating natural effect on exterior walls . Colorfast , its unique effect, and natural composition is the most attractive features of this product.

Recommended Use : it is specially designed for exterior application on concrete , gypsum & cement surfaces. It is suitable for exterior walls of hotels , showroom galleries, offices, palaces etc. It can be used for interior wall also.

### PHYSICAL DATA :-

Appearance	:	Natural Effect
colors	:	as per catalog
Specific gravity	:	Approx. 1.70
Solids by volume	:	Approx. 70%
Drying times at 30oC	:	Dust dry : approx. 60 minutes Full dry : approx. 24 hour
Flash point	:	Nonflammable

### APPLICATION DATA :

Application method	:	trowel
Type of thinner	:	Water
Percentage of thinner	:	not recommended
Dry film thickness per coat	:	700 microns.
Theor. Coverage at 700 microns DFT:	:	1 m2 / litre

### Surface Preparation:

All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence. For repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

### Application Method .:

1. prepare the surface properly and apply one coat of paintco latex Primer sealer
2. apply one coat of paintco Mishnu, by using recommended trowel and give enough time for dry

The above information is based on our practical experience, given in good faith. It does not constitute a guarantee for individual application because the application and handling in each case lie control. We cannot accept responsibility or liability for any damage also connection with the use of the product relative to coverage performance or injury.