

PAINTCO INDUSTRIAL Q.D. ENAMEL PAINT 1227

DESCRIPTION

- Paintco Industrial Q.D Enamel is based on special alkyd resin and has excellent adhesion and colour retention. It has good hiding power and suitable for interior and exterior use.. It is suitable for application on wood, steel work and concrete surfaces.

PHYSICAL DATA

Pigments	:	Rutile titanium dioxide and / or colour Pigments.
Appearance	:	gloss/s-gloss/matt
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.03
Solids by volume	:	Approx. 44%
Drying time at 30°C	:	Dust dry : approx. 1 hours Hard dry : 12 hours Next coat : overnight
Flash point	:	39°C

APPLICATION DATA

Application method	:	Airless spray , air spray brush and roller
Airless spray data	:	Nozzle 0.011 , Pressure 110- 150 kg / cm ²
Thinner	:	Thinner No. 211
Percentage of thinner	:	Air less spray : 5% max. by volume. Air spray : 15% max. by volume Brush and roller : 10 % max. by volume.
Dry film thickness per coat	:	30 microns.
Theor. coverage at 30 microns DFT	:	14.7 m ² / litre

REMARKS

Priming coats

- On steel and wood surfaces Paintco Industrial Quick Dry Primer 3213 is to be applied.
- Airless spray information is subject to adjustment and is for guidance only. Clean tools with thinner no 211