

## PAINTCO ACRYLIC EMULSION SEMI GLOSS 7239

### DESCRIPTION

- Paintco Acrylic Emulsion Semi Gloss is scuff proof, washable and nonsaponifiable paint based on hard copolymer.
- Semi gloss appearance without the lingering smell of white spirit, non yellowing characteristic to prevent change in shade after ageing and eco-friendly nature lead to preferential selection of this product over conventional alkyd based products. It is ideally suitable for interior and exterior uses.
- In addition to cement and concrete this product is also suitable for wooden surfaces.

### PHYSICAL DATA

Pigment	:	Rutile Titanium dioxide and /or colour pigments and functional extenders.
Appearance	:	Semi gloss
Colours	:	White and colours
No. of components	:	One
Specific gravity	:	Approx. 1.2
Solids by volume	:	Approx. 34 %
Drying time at 30°C	:	Dust dry : approx. 30 minutes Hard dry : approx. 4 hours Recoatibility : after 4 hours
Flash point	:	Nonflammable

### APPLICATION DATA

Application method	:	Air spray, brush and roller
Type of thinner	:	Water
Percentage of thinner	:	Air spray : 10-15% max. by volume Brush & roller : 5% Max. by volume
Dry film thickness per coat	:	30 microns
Ther. coverage at 30 mic. DFT	:	11.3 m <sup>2</sup> / litre

### Surface Preparation :

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

### Priming coats:-

- Apply Paintco Latex Primer Sealer 1201. or Alkali Resistant Primer 1507. followed by Paintco Magna Wall Filler 10000. for Interior or Paintco Magna Spray Plaster Putty 20000. for exterior.
- Acrylic Emulsion semi gloss is extraordinary good for stain and burnish resistance.