

PAINTCO STONE PRIMER 1207

DESCRIPTION

- Paintco stone primer is outstanding waterborne, low odor, top quality based on acrylic polymer. It is primarily intended to prime and seal off new walls, as well as old painted surfaces. Feature of this product is high penetrating power and alkaline resistant.
- It is ideal exterior application as primer for stone finish on cement, plaster, concrete, gypsum board etc.

PHYSICAL DATA

Appearance	:	Flat
Colours	:	White.
Specific gravity	:	Approx. 1.30
Solids by volume	:	Approx. 28%
Drying times at 30oC	:	Dust dry : approx. 30 minutes Hard dry : approx. 1 hour Recoatibility : after 2 hour
Flash point	:	Nonflammable.

APPLICATION DATA

Application method	:	Brush, shortnap roller & spray
Type of thinner	:	Sweet Water
Percentage of thinner	:	20% max. by volume
Dry film thickness per coat	:	30 microns
Ther. Coverage at 30 mic. DFT	:	9.33 m ² /litre

- Paintco stone primer should be thinned with water before applying to walls to satisfy their water demand.
- The practical spreading rate may vary, depending on the porosity and roughness of the substrate.
- Clean all tools with water immediately after use.

Surface Preparation

- The surface should be free from grit, dirt and grease. Fill hairline cracks and minor voids with Paintco Stucco Putty 2241, or Paintco Magna Wall Filler 10000 (for interior surfaces) and Paintco Magna Spray Plaster Putty XL 20000. (for exterior surfaces). Sand with sand paper lightly and thereafter apply Paintco stone primer, thinned with water. For repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

Subsequent coat

- Paintco stone finish