

PAINTCO ACRYLIC EMULSION GLOSS 7240

DESCRIPTION

- Paintco Acrylic Emulsion Gloss is based on special hard copolymer and flow modifiers. It has Excellent colour retention and gloss retention which give always a new look to the painted surface after slight mopping with wet cloth. It is ideally suitable for interior and exterior uses. Flow and leveling are phenomenally good.

PHYSICAL DATA

Pigments	:	Rutile Titanium dioxide and /or colour pigments
Appearance	:	Gloss
Colour	:	White and colours
Number of components	:	One
Specific gravity	:	Approx. 1.20
Solids by volume	:	Approx. 33 %
Drying time at 30° C	:	Dust dry : approx. 30 minutes Hard dry : approx. 4 hours Next coat : After 4 hours
Flash point	:	Nonflammable

APPLICATION DATA

Application method	:	Air spray brush & Roller
Type of thinner	:	Water
Percentage of thinner	:	Airless spray : 10-15% max. by volume Brush & roller : 5% max. by volume
Dry film thickness per coat	:	30 microns
Theor. coverage at 30 microns DFT	:	approx 11 m ² /litres

Surface Preparation

- All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

Remarks

- Apply Paintco Latex Primer Sealer 1201 or Paintco Alkali Resistant Primer 1507 followed by Paintco wall filler 10000 for interior or Paintco Magna Plaster Putty 20000 for exterior.
- Paintco Acrylic Emulsion Gloss is extraordinary good for stain and burnish resistance.