

PAINTCO MAGNA WALL FILLER 10000

DESCRIPTION

- Paintco Magna Wall Filler is Acrylic copolymer based interior putty recommended for filling cracks, small dents, eliminating surface imperfections and smoothing plaster and concrete surface by developing high film thickness per coat.
- Paintco Magna Wall Filler is an optimally formulated use-friendly product to meet practical requirements of plaster and concrete painting. Ease of application, non-sagging properties at high film thickness, good filling and opacifying properties, balanced feathering and gumming properties of Paintco Magna Wall Filler.

PHYSICAL DATA

Pigments	:	Functional extenders
Appearance	:	Flat
Colour	:	Off White
No. of components	:	One
Solids by volume	:	Approx. 54%
Drying time at 30°C	:	Dust dry : approx. 30mins. (depending of WFT) Hard dry : Approx. 2 hours (depending of WFT) Recoat ability : after 2 hours
Flash point	:	Nonflammable

APPLICATION DATA

Application Method	:	Spatula and trowel
Type of thinner	:	Water
Percentage of thinner	:	Depends on the kind of use
Theore. Coverage	:	Approximately 3.2m ² /kg at 100microns

REMARKS

- The salient feature of this filler is excellent intercoat adhesion with verity of undercoats and finishing paint which is achieved by suitable combination of functional extenders.
- In addition to its normal use on cement and concrete structures.
- Use of following composite painting system is recommended.
 - Primer : Paintco Latex Primer Sealer 1201
 - Filler : Paintco Magna Wall Filler 10000
 - Finish : Paintco water based to conventional solvent based paint.