

PAINTCO NOVY 12015

DESCRIPTION :

Paintco Novy is a outstanding water borne decorative paint based on combination of special kind of acrylic binder and special effect pigment, which add an excellent appearance on walls .

It has good washability , color stability, excellent metallic effect resemble ornamented with a design of flowers and turns walls in to dignified beauty.

Recommended Use :

it is specially designed for interior application on concrete , gypsum & cement surfaces and can be applied on interior walls of hotels , showroom galleries, offices, palaces etc.

PHYSICAL DATA :-

Appearance	:	metallic glorious effect
colors	:	as per catalog
Specific gravity	:	Approx. 1.15
Solids by volume	:	Approx. 41%
Drying times at 30oC	:	Dust dry : approx. 15 minutes Full dry : approx. 24 hour Hard dry : 48 hours
Water Resistant	:	Passes 7 days ASTM D 870
Flash point	:	Nonflammable

APPLICATION DATA :

Application method	:	special trowel
Type of thinner	:	Water
Percentage of thinner	:	not recommended
Dry film thickness per coat	:	75 microns.
Theor. Coverage at 150 microns DFT:	:	2.7 m ² / litre

Surface Preparation:

All surfaces must be thoroughly prepared and clean and should be free from alkali and efflorescence, for repair and maintenance, remove damaged and loose paint by mechanical cleaning and dust off.

Application Method :

- prepare the surface properly and apply one coat of paintco latex primer sealer 1201 or paintco alkali resistant primer 1202
- apply one or two coats of paintco stucco putty 2241 or paintco wood and wall putty 2008
- apply one coat of paintco latex under coat
- apply two or three coats of paintco NOVY obliquely by using special recommended trowel and give enough time for each coat to dry fully

The above information is based on our practical experience, given in good faith. It does not constitute a guarantee for individual application because the application and handling in each case lie control. We can not accept responsibility or liability for any damage also connection with the use of the product relative to coverage performance or injury.